



RESILIENT | M²

**BUILT TO SERVE,
BUILT TO LAST**

PERFORMANCE DEFINED

TIRE LIFE



Trelleborg products guarantee **the best wear** performance in the industry.

This results in longer tire life, **additional hours of usage**, reduced downtime and lower maintenance costs.

ENERGY SAVING



Trelleborg is the **largest approved tire manufacturer to the OEMs**. We work closely with them to ensure we meet the requirements of energy consumption.

This results in **reduced fuel costs** for our customers.

STABILITY



Trelleborg products are designed to have **large footprints** giving a maximum contact area leading to better stability and even tire wear.

COMFORT




Trelleborg understands the requirements of a **safe working environment**. Our products are designed to reduce vibration and **keep noise to a minimum level**.


We follow the strictest regulations for work safety while providing a comfortable ride.

PERFORMANCE AGAINST PREMIUM COMPETITOR


TIRE LIFE



ENERGY SAVING



STABILITY




COMFORT



TRELLEBORG M²

The Trelleborg M² is the latest evolution of the Trelleborg range of solid tires combining all our knowledge and expertise in tire design and production. M² is designed to deliver exceptional performance over whole tire life in demanding environments offering enhance resistance to tire damage and wear resistance that sets it apart from other products in its class.

M² comes with the Pit Stop Line feature as standard.



| Tire Size | Rim | Pattern | LOC Version | Width [mm] | Overall Diameter [mm] | Counterbalanced Forklift Truck: load capacity up to 25 km/h | | Other Vehicles: load capacity @ 10 km/h [kg] |
|-----------|------------|-------------|-------------|------------|-----------------------|---|-------------------|--|
| | | | | | | Load Wheels [kg] | Steer Wheels [kg] | |
| 4.00-8 | 3.75P-8 | M2 | | 124 | 409 | 1010 | 775 | 915 |
| 15x4½-8 | 3.00D-8 | M2 - RIB | Yes | 117 | 376 | 1040 | 800 | 945 |
| 5.00-8 | 3.00D-8 | M2 | Yes | 122 | 457 | 1420 | 1090 | 1290 |
| 5.00-8 | 3.75P-8 | M2 - RIB | | 152 | 457 | 1495 | 1150 | 1360 |
| 16x6-8 | 4.33R-8 | M2 - RIB | Yes | 152 | 406 | 1495 | 1150 | 1360 |
| 18x7-8 | 4.33R-8 | M2 | Yes | 157 | 457 | 2145 | 1650 | 1950 |
| 140/55-9 | 4.00E-9 | M2 | Yes | 132 | 380 | 1170 | 900 | 1065 |
| 6.00-9 | 4.00E-9 | M2 - RIB | Yes | 140 | 526 | 1885 | 1450 | 1715 |
| 21x8-9 | 6.00E-9 | M2 | Yes | 185 | 518 | 2760 | 2120 | 2505 |
| 6.50-10 | 5.00F-10 | M2 | Yes | 160 | 577 | 2340 | 1800 | 2125 |
| 6.50-10 | 5.5-10 | M2 | | 160 | 577 | 2340 | 1800 | 2125 |
| 180/60-10 | 5.00F-10 | M2 | Yes | 157 | 458 | 2405 | 1850 | 2185 |
| 200/50-10 | 6.50F-10 | M2 | Yes | 191 | 457 | 2470 | 1900 | 2245 |
| 23x9-10 | 6.50F-10 | M2 | Yes | 201 | 584 | 3445 | 2650 | 3130 |
| 7.00-12 | 5.00S-12 | M2 - Smooth | Yes | 173 | 650 | 2915 | 2240 | 2645 |
| 23x10-12 | 8.00G-12 | M2 | Yes | 239 | 587 | 3770 | 2900 | 3425 |
| 27x10-12 | 8.00G-12 | M2 | Yes | 239 | 678 | 3900 | 3000 | 3540 |
| 315/45-12 | 10.00G-12 | M2 | Yes | 279 | 572 | 4485 | 3450 | 4075 |
| 7.00-15 | 5.5-15 | M2 | Yes | 180 | 729 | 3545 | 2725 | 3220 |
| 28x9-15 | 7.0-15 | M2 | Yes | 224 | 693 | 3900 | 3000 | 3540 |
| 7.50-15 | 5.5/6.5-15 | M2 | | 193 | 747 | 3900 | 3000 | 3540 |
| 250-15 | 7.0-15 | M2 | Yes | 224 | 711 | 4745 | 3650 | 4310 |
| 250-15 | 7.5-15 | M2 | | 224 | 711 | 4745 | 3650 | 4310 |
| 8.25-15 | 6.5-15 | M2 | Yes | 208 | 808 | 4745 | 3650 | 4310 |
| 355/50-15 | 9.75-15 | M2 | Yes | 284 | 711 | 5690 | 4375 | 5165 |
| 300-15 | 8.0-15 | M2 | Yes | 257 | 813 | 5850 | 4500 | 5310 |
| 355/65-15 | 9.75-15 | M2 | Yes | 282 | 808 | 7800 | 6000 | 7080 |
| 7.50-16 | 5.5-16 | M2 | | 208 | 808 | 4000 | 3075 | 3630 |
| 9.00-20 | 6.5-20 | M2 | | 221 | 973 | 5400 | 4500 | 4905 |
| 10.00-20 | 6.5-20 | M2 | | 249 | 1011 | 5850 | 4875 | 5315 |
| 10.00-20 | 8.0-20 | M2 | | 249 | 1011 | 6000 | 5000 | 5450 |
| 12.00-20 | 8.0-20 | M2 - Smooth | | 259 | 1092 | 7560 | 6300 | 6870 |
| 12.00-20 | 8.5-20 | M2 | | 259 | 1092 | 7560 | 6300 | 6870 |
| 12.00-20 | 10.0-20 | M2 - Smooth | | 312 | 1090 | 7800 | 6500 | 7085 |
| 355/50-20 | 10.0-20 | Smooth | Yes | 310 | 833 | 8280 | 6900 | 7525 |

*In accordance to ETRTO Standard

AVAILABLE ADDITIONAL COMPOUNDS

