



RESILIENT | **PREMIA**

LONG LASTING PERFORMANCE

PERFORMANCE DEFINED



TIRE LIFE

Trelleborg products guarantee **the best wear** performance in the industry. This results in longer tire life, **additional hours of usage**, reduced downtime and lower maintenance costs.



ENERGY SAVING

Trelleborg is the **largest approved tire manufacturer to the OEMs**. We work closely with them to ensure we meet the requirements of energy consumption. This results in **reduced fuel costs** for our customers.



STABILITY

Trelleborg products are designed to have **large footprints** giving a maximum contact area leading to better stability and even tire wear.



COMFORT

Trelleborg understands the requirements of a **safe working environment**. Our products are designed to reduce vibration and **keep noise to a minimum level**. We follow the strictest regulations for work safety while providing a comfortable ride.

PERFORMANCE AGAINST PREMIUM COMPETITOR

TIRE LIFE



ENERGY SAVING



STABILITY



COMFORT



TRELLEBORG PREMIA

Premia solid tires are designed for long lasting performance. The square footprint provides even wear and increased stability. The combination of advanced compounding and premium natural rubber combines to create a tire that has excellent heat resistance. Operating at lower temperatures reduces the risk of premature failures.

Premia is available in a wide range of sizes and special compounds. It's the reliable solution for all your material handling needs.



Premia

Counterbalanced Forklift Truck:
load capacity up to 25 km/h

Tire Size	Rim	Pattern	LOC Version	Width [mm]	Overall Diameter [mm]	Load Wheels [kg]	Steer Wheels [kg]	Other Vehicles: load capacity @ 10 km/h [kg]
5.00-8	3.00D-8	Premia	Yes	121	451	1420	1090	1290
15x4½-8	3.00D-8	Premia	Yes	115	380	1040	800	945
16x6-8	4.33R-8	Premia	Yes	151	412	1495	1150	1360
18x7-8	4.33R-8	Premia	Yes	146	457	2145	1650	1950
140/55-9	4.00E-9	Premia	Yes	130	381	1170	900	1065
6.00-9	4.00E-9	Premia	Yes	142	528	1885	1450	1715
21x8-9	6.00E-9	Premia	Yes	188	516	2760	2120	2505
6.50-10	5.00F-10	Premia	Yes	165	571	2340	1800	2125
200/50-10	6.50F-10	Premia	Yes	194	457	2470	1900	2245
23x9-10	6.50F-10	Premia	Yes	208	583	3445	2650	3130
7.00-12	5.00S-12	Premia	Yes	168	657	2915	2240	2645
23x10-12	8.00G-12	Premia	Yes	230	575	3770	2900	3425
27x10-12	8.00G-12	Premia	Yes	230	676	3900	3000	3540
7.00-15	5.5-15	Premia	Yes	186	723	3545	2725	3220
28x9-15	7.0-15	Premia	Yes	206	700	3900	3000	3540
7.50-15	6.5-15	Premia	Yes	189	754	3900	3000	3540
250-15	7.0-15	Premia	Yes	211	713	4745	3650	4310
250-15	7.5-15	Premia	Yes	211	713	4745	3650	4310
355/50-15	9.75-15	Premia	Yes	283	713	5690	4375	5165
355/45-15	9.75-15	Premia	Yes	287	692	5690	4375	5165
8.25-15	6.5-15	Premia	Yes	203	813	4745	3650	4310
300-15	8.0-15	Premia	Yes	241	814	5850	4500	5310
355/65-15	9.75-15	Premia	Yes	300	818	7800	6000	7080

*In accordance to ETRTO Standard

AVAILABLE ADDITIONAL COMPOUNDS

- 
NM
 NON MARKING
- 
ELCON
 ELCON
- 
HL
 HIGH LOAD
- 
SCRUBBER
 SCRUBBER
- 
CR
 CUT RESISTANT

