



PNEUMATIC | T-800

BALANCED PERFORMANCE

PERFORMANCE DEFINED



TIRE LIFE

Trelleborg products guarantee **the best wear** performance in the industry. This results in longer tire life, **additional hours of usage**, reduced downtime and lower maintenance costs.



STABILITY

Trelleborg tires are designed with **exceptional stability**. Our tires are engineered to ensure **proper distribution of heat** and to prevent excessive deflection under load.



ENERGY SAVING

Trelleborg is the **largest approved tire manufacturer to the OEMs**. We work closely with them to ensure we meet the requirements of energy consumption. This results in **reduced fuel costs** for our customers.



COMFORT

Trelleborg recognizes the importance of a **safe working environment**. Our products are designed to minimize vibration and **keep noise to a minimum level**. We follow the strictest regulations for work safety while providing a comfortable ride.

TRELLEBORG T-800

The T-800 pneumatic tire range has been developed to deliver good performance at a competitive price for forklifts and other industrial equipment. The specific lug tread pattern provides optimal grip and traction. The cross-ply/diagonal structure insures high stability and comfort.

The T-800 is available in popular sizes.



T-800

Tire Size	PR	Rim	Pattern	Tire Weight	Tread Depth	Width	Overall Diameter	Inflation Pressure	Counterbalanced Forklift Truck: load capacity up to 25km/h		Other Vehicles: load capacity @ 10 km/h
									Load Wheels	Steer Wheels	
				[kg]	[mm]	[mm]	[mm]	[bar]	[kg]	[kg]	[kg]
15x4½-8	8	3.25-8	T-800	5.5	8	122	385	7.2	690	530	690
5.00-8	10	3.00D-8	T-800	5.5	13	135	465	10.0	1415	1090	1415
18x7-8	16	4.33R-8	T-800	7.7	17	160	453	10.0	2145	1650	2145
6.00-9	12	4.00E-9	T-800	9.1	13	155	540	10.0	1885	1450	1885
21x8-9	14	6.00E-9	T-800	11.8	18	204	536	9.0	2535	1950	2535
6.50-10	10	5.00F-10	T-800	11.4	14	183	597	7.8	1950	1500	1950
23x9-10	20	6.50F-10	T-800	17.3	19	228	585	10.0	3445	2650	3445
27x10-12	14	8.00G-12	T-800	21.3	21	245	691	7.0	3545	2725	3545
7.00-12	14	5.00S-12	T-800	15.9	15	196	685	9.0	2755	2120	2755
7.00-15	14	5.5-15	T-800	20.0	17	190	755	9.3	3250	2500	3250
7.50-15	14	6.0-15	T-800	23.2	17	215	808	9.3	3640	2800	3640
28x9-15 (8.15-15)	14	7.0-15	T-800	21.8	20	217	722	10.0	3900	3000	3900
8.25-15	14	6.5-15	T-800	29.1	18	255	834	8.0	4225	3250	4225
250-15	20	7.0-15	T-800	29.1	21	240	760	10.3	5070	3900	5070
300-15	20	8.0-15	T-800	41.4	25	290	840	9.4	6565	5050	6565
10.00-20	16	8.0-20	T-800	52.5	23	278	1073	7.9	6085	5140	6085
12.00-20	18	8.0-20	T-800	75.5	25	315	1146	8.9	8360	6430	8360
12.00-20	22	8.0-20	T-800	78.8	22	315	1146	10.5	9455	7275	9455

